

SAFETY DATA SHEET

CELCURE M65 + MICROSHADES TREATED TIMBER

Page: 1

Compilation date: 13/09/2017

Revision date: 13/09/2017

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: CELCURE M65 + MICROSHADES TREATED TIMBER

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Protim Solignum Ltd

Fieldhouse Lane

Marlow

Buckinghamshire

SL7 1LS

United Kingdom

Tel: +44 (0) 1628 486 644

Fax: +44 (0) 1628 476 757

Email: kpc@koppers.eu

1.4. Emergency telephone number

Emergency tel: +44 (0) 1628 890 907

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Chronic 2: H411

Most important adverse effects: Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H411: Toxic to aquatic life with long lasting effects.

Hazard pictograms: GHS09: Environmental



Precautionary statements: P260: Do not breathe dust.

P264: Wash hands thoroughly after handling.

P280: Wear protective gloves.

SAFETY DATA SHEET

CELCURE M65 + MICROSHADES TREATED TIMBER

Page: 2

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

SOFT WOOD DUST

EINECS	CAS	PBT / WEL	CLP Classification	Percent
-	-	Substance with a Community workplace exposure limit.	-	70-90%

COPPER(II) CARBONATE-COPPER(II) HYDROXIDE (1:1)

-	12069-69-1	-	Acute Tox. 4: H302+332; Eye Irrit. 2: H319; Aquatic Acute 1: H400; Aquatic Chronic 1: H410	<1%
---	------------	---	--	-----

SODIUM NITRITE.

231-555-9	7632-00-0	-	Ox. Sol. 3: H272; Acute Tox. 3: H301; Aquatic Acute 1: H400	<1%
-----------	-----------	---	---	-----

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

Inhalation: Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

[cont...]

SAFETY DATA SHEET

CELCURE M65 + MICROSHADES TREATED TIMBER

Page: 3

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Mark out the contaminated area with signs and prevent access to unauthorised personnel.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid the formation or spread of dust in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep treated timber dry.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

SOFT WOOD DUST

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	5 mg/m ³	-	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Respiratory protection: When sawing wood: Respiratory protective device with particle filter.

Hand protection: Protective gloves.

[cont...]

SAFETY DATA SHEET

CELCURE M65 + MICROSHADES TREATED TIMBER

Page: 4

Eye protection: When sawing wood: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Solid

Colour: Light Brown

Odour: Odourless

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions. Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

COPPER(II) CARBONATE-COPPER(II) HYDROXIDE (1:1)

ORAL	RAT	LD50	1434	mg/kg
------	-----	------	------	-------

SODIUM NITRITE.

ORAL	MUS	LD50	175	mg/kg
------	-----	------	-----	-------

[cont...]

SAFETY DATA SHEET

CELCURE M65 + MICROSHADES TREATED TIMBER

Page: 5

ORAL	RAT	LD50	180	mg/kg
SCU	RAT	LD50	96600	µg/kg

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

COPPER(II) CARBONATE-COPPER(II) HYDROXIDE (1:1)

Daphnia magna	48H EC50	25.0	µg/l
---------------	----------	------	------

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

[cont...]

SAFETY DATA SHEET

CELCURE M65 + MICROSHADES TREATED TIMBER

Page: 6

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H272: May intensify fire; oxidiser.

H301: Toxic if swallowed.

H302+332: Harmful if swallowed or if inhaled.

H319: Causes serious eye irritation.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.